



| | | |
|---|----------------|---|
| Anziehvorschrift für Zylinderkopf | 122.810 |  Das Original |
| Tightening Instructions for Cylinder Head | | |
| Instructions de serrage pour culasse | | |
| Prescripciones de apriete para culatas | | |
| passend für / suitable for adaptable à / adaptable a | | Mercedes-Benz |

Schraubenkopf / Head shape Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete
Tête de vis / Cabeza de tornillo



456.111

M 12x102x1,75

| | | |
|---|-----------------------------------|-------------------------|
| Anziehen/ Tightening/ Serrage/ Apriete | M 12 * 55 Nm ➤ 90° ➤ 90° | M 8 ➤ 18 Nm ➤ 90° |
|---|-----------------------------------|-------------------------|

Zeichenerklärung / Explanations / Explication / Explicacion

| | | | | |
|---|---|------------------------------|--------------------------------|---------------------------------------|
| * | neue Zylinderkopfschrauben verwenden | use new cylinder head bolts | utiliser des vis neuves | emplar tornillos nuevos |
| ★ | Warmlauf (80°C) | warm up time (80°C) | chauffage (80°C) | calentamiento (80°C) |
| □ | Schrauben einzeln lösen und wieder anziehen | loosen and tighten each bolt | deserrer et serrer vis par vis | aflojar y apretar tornillo a tornillo |
| ● | Setzzeit | relaxation time | durée de tassement | tiempo de espera |
| ➤ | Drehwinkel | torque angle | angle de serrage | ángulo de giro |

Motortyp / Engine type / Type de moteur / Tipo de motor

Ø 89,9

Mot: M111.940-948,951,952,955-958,960,961

93-141 KW (126 - 192 PS)

W202 C180, C200/W124 E200, E220

W203 C180, C200/W210 E200

R170 SLK200/C208 CLK200

Vito 638

ElringKlinger AG, Max-Eyth-Str.2
72581 Dettingen / Erms. Tel. 07123/724 601

122.810