



DEXRON III

**Fluid for automatic gearboxes
Power steering systems
Torque converters and hydraulic systems**

Technosynthese®

TYPE OF USE

Automatic Transmission Fluid (ATF) for all systems where DEXRON or MERCON standard is required.

Automatic gearboxes, torque converters, power steering systems, boat reversing gears, hydrostatic transmissions and hydraulic or mechanical systems that require DEXRON or MERCON standards.

PERFORMANCES

APPROVALS	MAN 339 Typ Z1 & V1 MB-Approval 236.9 VOITH 55.6335.32 (G607) ZF TE ML – 03D / 04D / 14A / 17C
PERFORMANCE	GENERAL MOTORS DEXRON III G FORD MERCON MB 236.5 ALLISON C-4 – CATERPILLAR TO-2

More fluid at low temperature than Dexron IIE oils, allows easier gear change in cold weather.
Higher oxidation resistance than Dexron IIE standard.
Oil film stability under high temperature.
Anti-wear, Anti-corrosion, Anti-foam.

RECOMMENDATION

MOTUL DEXRON III can be used (and mixed) for applications where "DEXRON", "B DEXRON", "DEXRON II D", "DEXRON IIE", or "DEXRON III" is required.

Oil change: according to manufacturers' recommendations and to be adapted according to your own use.

PROPERTIES

Color	Visual	Red
Density at 20°C (68°F)	ASTM D1298	0.861
Viscosity at 40°C (104°F)	ASTM D445	34.1 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	7.2 mm ² /s
Viscosity index	ASTM D2270	182
Flash point	ASTM D92	201°C / 394°F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - Web Site: www.motul.com

04/15