

AirGuard

Wheel Sensor, TPMS

This snap-in wheel sensor can be installed in both light alloy rims and steel rims and can be activated wirelessly. Please note that the permissible maximum speed is restricted to 210 km/h. Supplied with a rubber valve. Herth+Buss wheel sensors can be used in all vehicles that have a tyre pressure monitoring system installed as standard. The AirGuard is required for programming and adjustment to the vehicle concerned. This process only takes between 5 and 15 seconds per sensor. An outstanding feature of the Herth+Buss wheel sensors: the original serial/ID number can be

copied from the "old" sensor to the new one, or can be reassigned. In addition, the wheel sensors can be rewritten, and can be used in aluminium and steel rims. The sensors can be ordered individually and are supplied with a complete valve. A replacement valve is also available.

- one for all: optimum stockage with just one universal wheel sensor
- for steel or aluminium rims
- certification up to 210 km/h
- battery service life: 3-7 years

Material: Steel Elastomer
Pressure: to 9 bar
Weight: 36 g
only in connection with: 95990001

Info: with battery
 with pressure sensor
 with integrated air temperature sensor
 with screw
 with valves

Frequency Range MHz	Colour	DU	Article no.
433	●	1	70699434
Content			QU
Valve, TPMS AirGuard			1 70699434013
Accessories		see	DU
Programming-/Diagnostic Unit, TPMS AirGuard		Katalog08	1 95990001

